



## STEP 1 – PRIOR TO INSTALLATION

- A) Bushwacker®** only approves installing the flares according to these written instructions with the hardware provided. **WARNING:** Failure to install according to these instructions will invalidate the warranty. This includes, but is not limited to using alternative installation methods, hardware, or materials. **DO NOT USE:** Loctite, SuperGlue, or similar products on the hardware or the flares.
- B) Fit:** Verify the fit of the flares to vehicle. (Some filing, sanding, or cutting may be necessary to ensure proper fit).
- C) Painting:** (Optional) if paint is desired it must be done prior to installing flares on vehicle. Clean outer surface with a good grade degreaser. **DO NOT USE LACQUER THINNER OR ENAMEL REDUCER AS A DEGREASER.** Wipe outer surface thoroughly with a tack rag prior to paint. Application of plastic adhesion promoter for ABS plastic as per your paint system manufacturer's recommendations is required. Paint flares using a high quality enamel, or polyurethane automotive paint. If painting edge trim (not recommended), use a flex additive.
- D) Performance:** Using larger Tires may increase the area required to turn the vehicle. Some Tire/Rim combinations may require lowering bump stops and or installing steering stops to prevent tire from contacting flare.
- E) Exhaust System:** Modifications may be necessary to maintain a minimum 4" clearance between flares and exhaust pipes. (Exhaust gases should not vent directly onto flares)
- F) Metal Protection:** All exposed fasteners and bare metal should be treated with rust resistant paint **BEFORE** installing flares. Spray inner fender wells with undercoating **AFTER** flare attachments have been completed.
- G) Decals:** Flares may interfere with existing decals on vehicle. If you wish, remove decals prior to installation of flares.
- H) Care & Cleaning:** Bushwacker fender flares are built to last; any detergent you use to wash your vehicle is sufficient to clean the flare. Do not use any harsh abrasive detergents.

# RAM DRT Style® Fender Flares Set of 4

Set Part #50932-02

Rev-1 05/28/2019

For complete fitment info visit : [www.bushwacker.com](http://www.bushwacker.com)

## TOOLS FOR EASY INSTALLATION:

- Utility Knife
- #2 Phillips Driver
- Socket Wrench
- 8 mm Socket
- 1/2" Wrench
- Awl or Similar Pointed Tool

**PLEASE READ:** Dirt and debris can become lodged between the fender flares and the vehicle's fenders, causing scratching and paint wear from vibration. Lund International is not responsible for any damage, and the installation of our fender flares is done with the buyer's understanding that this scratching and paint wear may occur.

## LIMITED LIFETIME WARRANTY AGAINST ANY MANUFACTURING DEFECTS

- To claim a warranty, you must provide Proof of Purchase.



The material that your product is made from can be recycled. Please also consider recycling the packaging that your product came in.



## Included in Hardware Kit:

1.



CL1-0022,  
#10 "U" Clip,

6 pcs

2.



SW1-0056,  
#8 x 3/4"  
PH Screw,

6 pcs

3.



MT1-0014,  
1" x1.5" x.01"  
Black Mylar Tab,

6 pcs

4.



ET1-0002,  
Edge Trim Tool,

1 pc

5.



GP1-0025,  
EX4008 Wiper  
Style Edge Trim,  
340 inches

## STEP 2 - EDGE TRIM INSTALLATION

- A) Peel two to three inches of red vinyl backing away from Edge Trim (GP1-0025) tape. Applying the adhesive side of the edge trim to the inner side of the flare, affix the edge trim to the top edge of the flare (the portion that comes in contact with the vehicle).
- B) Press edge trim into place along the top edge of the flare in one-foot increments, pulling red vinyl backing free as you continue to work your way around the top edge of the flare.




## Front Flare Installation Procedures (Passenger's Side):




Remove and retain four factory installed screws with 8 mm socket wrench. These screws will be reinstalled in a later step.




If you encounter a fit problem, remove inner piece at bottom rear of wheel well.




Install (2) Clips (CL1-0022) at this locations. See step 7, 8, 9, & 10.



At location in step 3, there is a lip with two factory holes. One hole is a circle and one is an oval. The Tab (MT1-0014) and Clip (CL1-0022) will be installed over the oval. The oval is the hole more toward the front of the vehicle.




Install Tab (MT1-0014) over existing factory hole. There are two holes at the top center location. Refer to step 4 for proper hole for installation.



Install Clip (CL1-0022) over Tab (MT1-0014).




Using an awl or similar pointed tool, poke a hole through Tab (MT1-0014) using the Clip (CL1-0022) hole as a guide.



Hold flare to vehicle and start the supplied screws (SW1-0056) with a Phillips screwdriver. *Do not tighten.*



Reinstall 4 screws with an 8mm socket that were removed in Step 1. Press firmly on flare and tighten all screws.




Completed front flare installation.

# Rear Flare Installation Procedures (Passenger's Side):



If you encounter a fit problem, remove inner piece at bottom rear and front of wheel well.



Remove inner piece at bottom rear of wheel well using a pry tool.




Remove these six factory installed screws using an 8mm socket wrench. X's indicate a factory screw that will not be removed.



Install Clip (CL1-0022) in this location. See Step 15.



Install plastic tab over existing factory hole.



Install Clip (CL1-0022) over existing hole.




17

Using an awl or similar pointed tool, poke a hole through Tab (MT1-0014) using the Clip (CL1-0022) hole as a guide.




18

Start supplied screw (SW1-0056) using a Phillips screwdriver. *Do not tighten.*



19

Hold flare in place while you start previously removed factory screws using an 8mm socket. *Do not tighten.*



20


Press firmly on flare and tighten all screws.




21

Completed rear flare installation.

## Edge Trim Tool Procedures:



Using supplied Edge Trim Tool (ET1-0002), seat edge trim against vehicle by hooking curved end under edge trim at one end of flare. Next, slide around outer edge of flare to the other end.



Using flat end of supplied Edge Trim Tool (ET1-0002), seat edge trim against flare by inserting straight end between edge trim and flare at one end. Next, slide around entire edge to the other end.